

AMENDMENT AND PRESENTATION OF CLAIMS

Please replace all prior claims in the present application with the following claims.

1. (Currently Amended) A method, comprising:
receiving at a mobile wireless event handling device, a first signal via a first network, from a monitoring device on a patient separate from the mobile wireless event handling device,
the monitoring ~~adapted to convey information relating to physiological parameters,~~ the first signal comprising at least a general broadcast emergency signal and including information corresponding to ~~the~~ physiological parameters and an identification of the monitoring device; and
transmitting from the mobile wireless event handling device to a ~~[[target]]~~ third party, a second signal via a second network, the second signal including at least information corresponding to the identification of the monitoring device.
2. (Original) The method of claim 1, wherein the monitor is an implant.
3. (Original) The method of claim 1, wherein the monitor is adapted to detect, sense, or measure the physiological parameters.
4. (Original) The method of claim 1, wherein the monitor is adapted to stimulate, intervene, or control physiological functions affecting the physiological parameters.
5. (Original) The method of claim 1, wherein the physiological parameters relate to heart function.

6. (Original) The method of claim 1, wherein the physiological parameters relate to brain function.

7. (Original) The method of claim 1, wherein the first signal and the second signal are wireless signals.

8. (Previously Presented) The method of claim 7, wherein the first network and the second network are wireless communication networks.

9. (Previously Presented) The method of claim 8, wherein the second network is a cellular network.

10. (Original) The method of claim 1, further comprising:
processing the first signal prior to transmitting the second signal.

11. (Currently Amended) The method of claim 10, wherein processing further comprises:
verifying a source of the first signal;
identifying an event associated with the first signal and related to the physiological parameters; and
determining the [target] third party for the second signal.

12. (Previously Presented) A system for handling an event, comprising:
a monitoring device, on a patient, configured to convey information relating to one or more physiological parameters, the monitoring device being further adapted to transmit a signal

via a first network, the signal comprising at least a general broadcast emergency signal and including information corresponding at least to an identification of the monitoring device; and

a mobile wireless event handling device, separate from the patient, configured to receive signals from the monitoring device including information corresponding to the identification of the monitoring device, the mobile wireless event handling device being further adapted to transmit a signal to a [[target]] third party, the signal including information corresponding to the identification of the monitoring device via a second network.

13. (Original) The system of claim 12, wherein the monitoring device is implanted in a human body.

14. (Original) The system of claim 12, wherein the monitoring device is adapted to detect, sense, or measure the physiological parameters.

15. (Original) The system of claim 12, wherein the monitoring device is adapted to stimulate, intervene, or control physiological functions affecting the physiological parameters.

16. (Original) The system of claim 12, wherein the physiological parameters relate to heart function.

17. (Original) The system of claim 12, wherein the physiological parameters relate to brain function.

18. (Previously Presented) The system of claim 12, wherein the monitoring device is adapted to transmit wireless signals.

19. (Original) The system of claim 12, wherein the monitoring device is adapted to transmit a signal when one or more physiological parameters satisfies a predetermined criteria.

20. (Original) The system of claim 12, wherein the monitoring device is adapted to transmit signals on a substantially continuous basis.

21. (Previously Presented) The system of claim 12, wherein the mobile wireless event handling device is adapted to transmit signals when one or more physiological parameters satisfies a predetermined criteria.

22. (Previously Presented) The system of claim 12, wherein the mobile wireless event handling device is adapted to transmit wireless signals via a second network.

23. (Currently Amended) The system of claim 12, wherein the mobile wireless event handling device comprises:

a data processing module adapted to verify a source of signals received, the data processing module being further adapted to identify an event associated with received signals and to determine the [[target]] third party for transmitted signals.

24-32. (Canceled)

33. (Currently Amended) ~~A mobile wireless event handling device,~~ An apparatus comprising:
at least one processor; and
at least one memory including computer program code,
the at least one memory and the computer program code configured to, with the at least one
processor, cause the apparatus to perform at least the following,
~~a receiving module configured to~~ receive signals via a first wireless network, the signals
comprising at least a general broadcast emergency signal and including information
corresponding to ~~the~~ physiological parameters and an identification of ~~[[the]]~~ a monitor
on a patient separate from the mobile wireless event handling device, the general
broadcast emergency signal being adapted for receipt by all mobile devices within
communication range of the ~~[[monitor]]~~ patient and being equipped with at least minimal
event handling capabilities~~[[;]]~~, and
~~a transmitting module configured to~~ transmit signals to a ~~[[target]]~~ third party, the signals
including at least information corresponding to the identification of the monitor via a
second network.

34. (Currently Amended) The ~~device~~ apparatus of claim 33, wherein the monitor is adapted
to detect, sense, or measure the physiological parameters.

35. (Currently Amended) The ~~device~~ apparatus of claim 33, wherein the monitor is adapted
to stimulate, intervent, or control physiological functions affecting the physiological parameters.

36. (Currently Amended) The ~~device~~ apparatus of claim 33, wherein the ~~transmitting module is adapted to transmit~~ signals are transmitted when one or more physiological parameters satisfies a predetermined criteria.

37. (Currently Amended) The ~~device~~ apparatus of claim 33, wherein the ~~transmitting module is adapted to transmit~~ signals are transmitted as wireless signals via the second network.

38. (Currently Amended) The ~~device~~ apparatus of claim 33, ~~further comprising:~~ wherein the apparatus is further cause, at least, to:

~~a data processing module adapted to verify a source of the received signals received by the receiving module, the data processing module being further adapted to identify an event associated with the received signals received by the receiving module , and to determine the [target] third party for the transmitted signals transmitted by the transmitting module.~~

39. (Currently Amended) A program product, comprising machine readable program code for causing a mobile wireless event handling device to perform the following steps:

receiving a first signal ~~in the~~ at a mobile wireless event handling device from a monitor on a patient separate from the mobile wireless event handling device ~~adapted to convey information related to physiological parameters~~ via a first network, the first signal comprising at least a general broadcast emergency signal and including information corresponding to ~~the~~ physiological parameters and an identification of the monitor, the general broadcast emergency signal being adapted for receipt by all mobile devices within

communication range of a source of the first signal and being equipped with at least minimal event handling capabilities; and

transmitting a second signal via a second network to a [[target]] third party, the second signal including at least information corresponding to the identification of the monitor.

40. (Previously Presented) The method of claim 1, wherein the second signal further includes identification of the mobile wireless event handling device.

41. (Previously Presented) The method of claim 1, wherein the first signal comprises a broadcast communication device.

42. (Previously Presented) The method of claim 1, wherein the general broadcast emergency signal is adapted for receipt by all mobile wireless event handling devices within communication range of the monitoring device.

43. (Previously Presented) The method of claim 42, wherein the mobile wireless event handling devices are equipped with at least minimal event handling capabilities for receiving the general broadcast emergency signal.

44. (Previously Presented) The method of claim 1, wherein the mobile wireless event handling devices includes at least minimal event handling capabilities for receiving the general broadcast emergency signal.

45. (Previously Presented) The system of claim 12, wherein the general broadcast emergency signal is adapted for receipt by all mobile devices within communication range of the monitoring device and being equipped with at least minimal event handling capabilities.

46. (Canceled)

47. (Previously Presented) The method of claim 1, wherein the first signal further includes information conveying location of the monitoring device.

48. (Previously Presented) The system of claim 12, wherein the signal further includes information conveying location of the monitoring device.

49. (Canceled)

50. (Previously Presented) The device of claim 33, wherein the signal further includes information conveying location of the monitoring device.

51. (Previously Presented) The program product of claim 39, wherein the signal further includes information conveying location of the monitoring device.